
## INDIGO

## **BRIKPRO 2 A**

- Wall lamp for outdoor lighting.
- Black silk-screened glass diffusers.
- Asymmetric beams.
- Direct/indirect lighting.
- Non-dimmable converter built in the device.

This product contains 2 light source(s) of energy efficiency F.





| CODE          | COLOR        | MATERIAL       | AC      | LED   | T° (K) | LED Lumen | System Lumen |
|---------------|--------------|----------------|---------|-------|--------|-----------|--------------|
| BP22/2C/3K/A  | ANTHRACITE   | CAST ALUMINIUM | AC 230V | 2x14W | 3000K  | 2x1300 Lm | 2x940 Lm     |
| BP22/2C/3K/G  | MATTE GREY   | CAST ALUMINIUM | AC 230V | 2x14W | 3000K  | 2x1300 Lm | 2x940 Lm     |
| BP22/2C/3K/W  | MATT WHITE   | CAST ALUMINIUM | AC 230V | 2x14W | 3000K  | 2x1300 Lm | 2x940 Lm     |
| BP22/2C/3K/BR | CORTEN STEEL | CAST ALUMINIUM | AC 230V | 2x14W | 3000K  | 2x1300 Lm | 2x940 Lm     |





Wall mounting only. This lamp illuminates on 2 areas.



Indoor and outdoor use.



Dust-tight. Watertight (immersible).



Protection against an impact energy of 20 Joules.



Earth wire . Fixture equipped with primary insulation only.



Beam 40°.



Product in conformity CE.



Colour rendering index >90.



LED LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.



5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Non-replaceable control gear.



Non-replaceable light source.