


BRIKPRO 2

- Wall lamp for outdoor lighting.
- Opaline glass diffusers.
- Direct/indirect lighting.
- Non-dimmable converter built in the device.

This product contains 2 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
BP12/2D/3K/A	ANTHRACITE	CAST ALUMINIUM	AC 230V	2x7W	3000K	2x870 Lm	2x695 Lm
BP12/2D/3K/G	MATTE GREY	CAST ALUMINIUM	AC 230V	2x7W	3000K	2x870 Lm	2x695 Lm
BP12/2D/3K/W	MATT WHITE	CAST ALUMINIUM	AC 230V	2x7W	3000K	2x870 Lm	2x695 Lm
BP12/2D/3K/BR	CORTEN STEEL	CAST ALUMINIUM	AC 230V	2x7W	3000K	2x870 Lm	2x695 Lm



ANTHRACITE




MATTE GREY





MATT WHITE





CORTEN STEEL

 Wall mounting only. This lamp illuminates on 2 areas.


 Indoor and outdoor use.


 IP 67 Dust-tight. Watertight (immersible).


 IK 05 Protection against an impact energy of 0,70 Joule.


 Earth wire . Fixture equipped with primary insulation only.


 Beam 80°.


 CE Product in conformity CE.


 CRI >90 Colour rendering index >90.


 LED L70B20 50,000h LED specifications.


 RG1 Photobiological risk RG1


 650° Test on 650°.

 Power supply included.

 5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Non-replaceable control gear.

 Non-replaceable light source.