




















BASIL 3 P


- Accent spotlight for outdoor lighting.
 - Adjustable stem height: 60 or 90cm.
 - Adjustable spotlight position.
 - 2.50m cable and ground spike included.
 - Non-dimmable converters integrated into the luminaire.
- This product contains 3 light source(s) of energy efficiency E.




CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
OU519WW05	MATT BLACK	ALUMINIUM	AC 230V	3x4W	3000K	3x475 Lm	3x295 Lm

ACCESSOIRES	DESCRIPTION	
OU48405	CONNECTOR 2PIN IP68	
OU48505	CONNECTOR 3PIN IP68	

-  Ground mounting only.
-  Outdoor use.
-  Protected against the ingress of dust. Protected against jets of water.
-  Protection against an impact energy of 2 Joules.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Vertical orientation maximum to 360°.
-  Horizontal orientation maximum to 360°.
-  Beam 50°.
-  Product in conformity CE.
-  Colour rendering index >80.
-  LED specifications.
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  5 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.