














C100924





CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Case T° Max.	Amb. T° Max.
C100924		DC 24V	DC 24V	2	4x1A	75°C	50°C
PR3011	4x8,4W	DC 24V	350mA		4x350mA	75°C	50°C
PR3002	4x39W	DC 24V	DC 24V		4x1,6A	75°C	50°C

ACCESSOIRES	DESCRIPTION	L (mm)	
RC2819	RF REMOTE CONTROL 6 ZONES RGB/RGBW	140	
WC2820BLK	RF WALL CONTROL 4 ZONES RGB/RGBW 230V	86	
WC2820WH	RF WALL CONTROL 4 ZONES RGB/RGBW 230V	86	
TR2818	WIFI RF TRANSMITTER 8 ZONES 24V	160	
CF505RGBW	RIBBON CABLE 4x0,3mm²-1x0,5mm² RGBW 1m		
CD173	DRIVER 30W 24V CV	153	
CD174	DRIVER 60W 24V CV	180	
CD175	DRIVER 75W 24V CV	180	
CD176	DRIVER 120W 24V CV	300	
CD177	DRIVER 180W 24V CV	345	

 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.

 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

 Product in conformity CE.

 The product is dimmable.



Colour change RGB.



RGB + White.



Connect to a constant voltage LED power supply of 24VDC.



3 years warranty.

