


# GL016 SQ

This product contains 1 light source(s) of energy efficiency F.



CODE	MATERIAL	DC	LED	T° (K)	System Lumen
GL016SQ27	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	70 Lm (350mA) 120 Lm (700mA)
GL016SQWW	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	75 Lm (350mA) 135 Lm (700mA)
GL016SQNW	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	95 Lm (350mA) 140 Lm (700mA)

ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)	
TUBE50	ALUMINIUM	INSTALLATION TUBE 56x150mm	150	
PSIP3509W		DRIVER 1-9W 350mA CC IP65	149	
PSIP35018W		DRIVER 9-18W 350mA CC IP65	149	
PSIP70018W		DRIVER 2-18W 700mA CC IP65	149	
PSIP70036W		DRIVER 18-36W 700mA CC IP65	162	
JB2		IP68 3-OUTLET SERIES JUNCTION BOX		
JB4		IP68 SERIES CONNECTION BOX WITH GEL		
JB6		IP68 CONNECTOR WITH GEL		
WCR275BLACK		H05RN-F CABLE 2x0.75mm² 1m		

Recessed floor mounting only.

Indoor and outdoor use.

Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).

Protection against an impact energy of 10 Joules.

Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.





Hole cut to insert luminaire (50mm)



Beam 25°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Power supply not included.



Series connection.



Connect to a constant current Led power supply of 350mA DC.




Connect to a constant current Led power supply of 700mA DC.



Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.



7 years warranty.



Replaceable control gear by an electrician.