


# GL016

This product contains 1 light source(s) of energy efficiency F.

of energy efficiency F.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	System Lumen
GL016BMBX27	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	70 Lm (350mA) 120 Lm (700mA)
GL016BMBX30	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	75 Lm (350mA) 135 Lm (700mA)
GL016BMBX40	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	95 Lm (350mA) 140 Lm (700mA)
GL016BMBXBL	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	BLUE	20 Lm (350mA) 20 Lm (700mA)
GL016F27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	70 Lm (350mA) 120 Lm (700mA)
GL016FWW	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	75 Lm (350mA) 135 Lm (700mA)
GL016FNW	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	95 Lm (350mA) 140 Lm (700mA)
GL016FBLUE	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	BLUE	10 Lm (350mA) 20 Lm (700mA)
GL016FAB27	ANTIQUÉ BRASS	ANTIQUÉ BRASS	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	70 Lm (350mA) 120 Lm (700mA)
GL016FABWW	ANTIQUÉ BRASS	ANTIQUÉ BRASS	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	75 Lm (350mA) 135 Lm (700mA)
GL016FABNW	ANTIQUÉ BRASS	ANTIQUÉ BRASS	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	95 Lm (350mA) 140 Lm (700mA)



BLACK



STAINLESS STEEL 316



















ANTIQUÉ BRASS

ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)	
TUBE50	ALUMINIUM	INSTALLATION TUBE 56x150mm	150	
PSIP3509W		DRIVER 1-9W 350mA CC IP65	149	
PSIP35018W		DRIVER 9-18W 350mA CC IP65	149	
PSIP70018W		DRIVER 2-18W 700mA CC IP65	149	
PSIP70036W		DRIVER 18-36W 700mA CC IP65	162	
JB2		IP68 3-OUTLET SERIES JUNCTION BOX		
JB4		IP68 SERIES CONNECTION BOX WITH GEL		

ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)
-------------	----------	-------------	--------

JB6		IP68 CONNECTOR WITH GEL	
-----	--	-------------------------	---

WCR275BLACK		H05RN-F CABLE 2x0.75mm² 1m	
-------------	--	----------------------------	---

-  Recessed floor mounting only.
-  Indoor and outdoor use.
-  IP68 Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).
-  IK09 Protection against an impact energy of 10 Joules.
-  Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.
-  Hole cut to insert luminaire (50mm)
-  Beam 25°.
-  Product in conformity CE.
-  CRI >80 Colour rendering index >80.
-  LED L70B10 70.000h LED specifications.
-  Power supply not included.
-  Series connection.
-  350 mA Connect to a constant current Led power supply of 350mA DC.
-  700 mA Connect to a constant current Led power supply of 700mA DC.
-  7 7 years warranty.
-  Replaceable control gear by an electrician.

