


# GL019 ULG

This product contains 1 light source(s) of energy efficiency F.



CODE	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	α
GL019DNBL27	STAINLESS STEEL 316	DC 350mA 3V	1W	2700K	80 Lm	70 Lm	12°
GL019DNBL30	STAINLESS STEEL 316	DC 350mA 3V	1W	3000K	90 Lm	74 Lm	12°
GL019DMBL27	STAINLESS STEEL 316	DC 350mA 3V	1W	2700K	80 Lm	60 Lm	30°
GL019DMBL30	STAINLESS STEEL 316	DC 350mA 3V	1W	3000K	90 Lm	64 Lm	30°

ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)
TUBE332	ALUMINIUM	INSTALLATION TUBE 37x150mm	150
PSIP3509W		DRIVER 1-9W 350mA CC IP65	149
PSIP35018W		DRIVER 9-18W 350mA CC IP65	149
JB2		IP68 3-OUTLET SERIES JUNCTION BOX	
JB4		IP68 SERIES CONNECTION BOX WITH GEL	
JB6		IP68 CONNECTOR WITH GEL	



Recessed floor mounting only.



Indoor and outdoor use.



Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).



Protection against an impact energy of 2 Joules.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (33 mm)



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Power supply not included.



Series connection.




Connect to a constant current Led power supply of 350mA DC.



Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.



**7** 7 years warranty.



Replaceable control gear by an electrician.