


GL019

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	System Lumen	α
GL019BNBX27	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	80 Lm (350mA) 130 Lm (700mA)	12°
GL019BNBX30	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	90 Lm (350mA) 150 Lm (700mA)	12°
GL019BNBX40	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	100 Lm (350mA) 180 Lm (700mA)	12°
GL019BNXB	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	BLUE	15 Lm (350mA) 25 Lm (700mA)	12°
GL019S27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	80 Lm (350mA) 130 Lm (700mA)	12°
GL019S27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	90 Lm (350mA) 150 Lm (700mA)	12°
GL019SNW	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	100 Lm (350mA) 180 Lm (700mA)	12°
GL019ANBX27	ANTIQU BRASS	ANTIQU BRASS	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	80 Lm (350mA) 130 Lm (700mA)	12°
GL019ANBX30	ANTIQU BRASS	ANTIQU BRASS	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	90 Lm (350mA) 150 Lm (700mA)	12°
GL019BWBX27	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	80 Lm (350mA) 130 Lm (700mA)	38°
GL019BWBX30	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	90 Lm (350mA) 150 Lm (700mA)	38°
GL019BWBX40	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	100 Lm (350mA) 180 Lm (700mA)	38°
GL019BWBXB	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	BLUE	15 Lm (350mA) 25 Lm (700mA)	38°
GL019F27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	80 Lm (350mA) 130 Lm (700mA)	38°
GL019F27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	90 Lm (350mA) 150 Lm (700mA)	38°
GL019FNW	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	100 Lm (350mA) 180 Lm (700mA)	38°
GL019FBLUE	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	BLUE	15 Lm (350mA) 25 Lm (700mA)	38°
GL019FRED	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	RED	35 Lm (350mA)	38°
GL019FAMBER	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	AMBER	20 Lm (350mA)	38°
GL019AWBX27	ANTIQU BRASS	ANTIQU BRASS	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	80 Lm (350mA) 130 Lm (700mA)	38°
GL019AWBX30	ANTIQU BRASS	ANTIQU BRASS	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	90 Lm (350mA) 150 Lm (700mA)	38°



BLACK


















STAINLESS STEEL 316



ANTIQU BRASS

ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)
TUBE332	ALUMINIUM	INSTALLATION TUBE 37x150mm	150
PSIP3509W		DRIVER 1-9W 350mA CC IP65	149
PSIP35018W		DRIVER 9-18W 350mA CC IP65	149



ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)
PSIP70018W		DRIVER 2-18W 700mA CC IP65	149
PSIP70036W		DRIVER 18-36W 700mA CC IP65	162
JB2		IP68 3-OUTLET SERIES JUNCTION BOX	
JB4		IP68 SERIES CONNECTION BOX WITH GEL	
 JB6	Recessed floor mounting only.	IP68 CONNECTOR WITH GEL	
	Indoor and outdoor use.		
	Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).		
	Protection against an impact energy of 2 Joules.		
	Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.		
	Hole cut to insert luminaire (33 mm)		
	Product in conformity CE.		
	Colour rendering index >80.		
	LED specifications.		
	Power supply not included.		
	Series connection.		
	Connect to a constant current Led power supply of 350mA DC.		
	Connect to a constant current Led power supply of 700mA DC.		
	7 years warranty.		
	Replaceable control gear by an electrician.		

