



# GL038


This product contains 1 light source(s) of energy efficiency E.





CODE	MATERIAL	AC	LED	T° (K)	System Lumen
GL038DWBM27	STAINLESS STEEL 316	AC 230V	2,9W	2700K	280 Lm
GL038DWBM30	STAINLESS STEEL 316	AC 230V	2,9W	3000K	290 Lm
GL038DWBM40	STAINLESS STEEL 316	AC 230V	2,9W	4000K	300 Lm
GL038AWBM27	ANTIQUÉ BRASS	AC 230V	2,9W	2700K	280 Lm
GL038AWBM30	ANTIQUÉ BRASS	AC 230V	2,9W	3000K	290 Lm




ACCESSOIRES	DESCRIPTION	
JB5	IP68 PARALLEL CONNECTION BOX WITH GEL	
WC59	IP68 CONNECTOR	


 Recessed floor mounting only.


 Indoor and outdoor use.

 IP67 Dust-tight. Watertight (immersible).


 IK08 Protection against an impact energy of 5 Joules.


 Earth wire . Fixture equipped with primary insulation only.


 Hole cut to insert luminaire. (80mm)


 Hole cut to insert recessed housing. (85mm).

 Beam 40°.

 Product in conformity CE.


 CRI >80 Colour rendering index >80.

 LED L70B10 70.000h LED specifications.


 Power supply included.



**7** 7 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.