


GL040 ULG

This product contains 1 light source(s) of energy efficiency E.



CODE	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	α
GL040DNBL27	STAINLESS STEEL 316	DC 350mA 6,5V	2W	2700K	240 Lm	200 Lm	12°
GL040DNBL30	STAINLESS STEEL 316	DC 350mA 6,5V	2W	3000K	270 Lm	208 Lm	12°
GL040ANBL27	ANTIQUÉ BRASS	DC 350mA 6,5V	2W	2700K	240 Lm	200 Lm	12°
GL040ANBL30	ANTIQUÉ BRASS	DC 350mA 6,5V	2W	3000K	270 Lm	208 Lm	12°
GL040DMBL27	STAINLESS STEEL 316	DC 350mA 6,5V	2W	2700K	240 Lm	200 Lm	34°
GL040DMBL30	STAINLESS STEEL 316	DC 350mA 6,5V	2W	3000K	270 Lm	208 Lm	34°
GL040DMBL40	STAINLESS STEEL 316	DC 350mA 6,5V	2W	4000K	280 Lm	215 Lm	34°
GL040AMBL27	ANTIQUÉ BRASS	DC 350mA 6,5V	2W	2700K	240 Lm	200 Lm	34°
GL040AMBL30	ANTIQUÉ BRASS	DC 350mA 6,5V	2W	3000K	270 Lm	208 Lm	34°



ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)
GLA01	STAINLESS STEEL 316	SQUARE RING 94x94mm	94
TUBE68	ALUMINIUM	INSTALLATION TUBE 72x150mm	150
PSIP3509W		DRIVER 1-9W 350mA CC IP65	149
PSIP35018W		DRIVER 9-18W 350mA CC IP65	149
JB2		IP68 3-OUTLET SERIES JUNCTION BOX	
JB4		IP68 SERIES CONNECTION BOX WITH GEL	
JB6		IP68 CONNECTOR WITH GEL	



Recessed floor mounting only.



Indoor and outdoor use.



Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).





Protection against an impact energy of 5 Joules.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (70mm)



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Power supply not included.




Series connection.



Connect to a constant current Led power supply of 350mA DC.



7 years warranty.



Replaceable control gear by an electrician.