


# GL040

This product contains 1 light source(s) of energy efficiency E.





CODE	MATERIAL	DC	LED	T° (K)	System Lumen	α
GL040DNBX27	STAINLESS STEEL 316	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	310 Lm (350mA) 515 Lm (700mA)	12°
GL040DNBX30	STAINLESS STEEL 316	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	3000K	290 Lm (350mA) 520 Lm (700mA)	12°
GL040DNBX40	STAINLESS STEEL 316	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	4000K	300 Lm (350mA) 530 Lm (700mA)	12°
GL040ANBX27	ANTIQUÉ BRASS	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	290 Lm (350mA) 515 Lm (700mA)	12°
GL040ANBX30	ANTIQUÉ BRASS	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	3000K	300 Lm (350mA) 520 Lm (700mA)	12°
GL040DWBX27	STAINLESS STEEL 316	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	290 Lm (350mA) 515 Lm (700mA)	40°
GL040DWBX30	STAINLESS STEEL 316	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	3000K	290 Lm (350mA) 520 Lm (700mA)	40°
GL040DWBX40	STAINLESS STEEL 316	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	4000K	300 Lm (350mA) 530 Lm (700mA)	40°
GL040AWBX27	ANTIQUÉ BRASS	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	290 Lm (350mA) 515 Lm (700mA)	40°
GL040AWBX30	ANTIQUÉ BRASS	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	3000K	300 Lm (350mA) 520 Lm (700mA)	40°




ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)
GLA01	STAINLESS STEEL 316	SQUARE RING 94x94mm	94
TUBE68	ALUMINIUM	INSTALLATION TUBE 72x150mm	150
PSIP3509W		DRIVER 1-9W 350mA CC IP65	149
PSIP35018W		DRIVER 9-18W 350mA CC IP65	149
PSIP70018W		DRIVER 2-18W 700mA CC IP65	149
PSIP70036W		DRIVER 18-36W 700mA CC IP65	162
JB2		IP68 3-OUTLET SERIES JUNCTION BOX	

ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)
-------------	----------	-------------	--------


JB4		IP68 SERIES CONNECTION BOX WITH GEL	
-----	--	-------------------------------------	---


 JB6	Recessed floor mounting only.	IP68 CONNECTOR WITH GEL	
--	-------------------------------	-------------------------	---

 Indoor and outdoor use.

 IP68 Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).

 IK08 Protection against an impact energy of 5 Joules.

 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

 Hole cut to insert luminaire (70mm)

 CE Product in conformity CE.

 CRI >80 Colour rendering index >80.

 LED L70B10 70.000h LED specifications.

 Power supply not included.

 Series connection.

 350 mA Connect to a constant current Led power supply of 350mA DC.

 700 mA Connect to a constant current Led power supply of 700mA DC.

 7 7 years warranty.

 Replaceable control gear by an electrician.