










# GL050

This product contains 1 light source(s) of energy efficiency F.



CODE	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
GL05027	STAINLESS STEEL 316	DC 350mA 8,5V	3W	2700K	240 Lm	46 Lm
GL050WW	STAINLESS STEEL 316	DC 350mA 8,5V	3W	3000K	250 Lm	46 Lm
GL050NW	STAINLESS STEEL 316	DC 350mA 8,5V	3W	4000K	260 Lm	50 Lm
GL050BLUE	STAINLESS STEEL 316	DC 350mA 8,5V	3W	BLUE		7 Lm

ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)	
GLA01	STAINLESS STEEL 316	SQUARE RING 94x94mm	94	
TUBE68	ALUMINIUM	INSTALLATION TUBE 72x150mm	150	
PSIP3509W		DRIVER 1-9W 350mA CC IP65	149	
PSIP35018W		DRIVER 9-18W 350mA CC IP65	149	
JB2		IP68 3-OUTLET SERIES JUNCTION BOX		
JB4		IP68 SERIES CONNECTION BOX WITH GEL		
JB6		IP68 CONNECTOR WITH GEL		
WCR275BLACK		H05RN-F CABLE 2x0.75mm² 1m		



Recessed floor mounting only.



Indoor and outdoor use.



Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).



Protection against an impact energy of 5 Joules.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.





Hole cut to insert luminaire (70mm)





Beam 100°.





 Product in conformity CE.


 Colour rendering index >80.


 LED specifications.


 Power supply not included.

 Series connection.

 Connect to a constant current Led power supply of 350mA DC.

 Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.

 7 years warranty.

 Replaceable control gear by an electrician.