










GL063


This product contains 3 light source(s) of energy efficiency F.





CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
GL063	CAST STAINLESS STEEL	STAINLESS STEEL 316	DC 350mA 8,5V	3W	3000K	90 Lm	45 Lm


ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)	
TUBE68	ALUMINIUM	INSTALLATION TUBE 72x150mm	150	
PSIP3509W		DRIVER 1-9W 350mA CC IP65	149	
PSIP35018W		DRIVER 9-18W 350mA CC IP65	149	
JB2		IP68 3-OUTLET SERIES JUNCTION BOX		
JB4		IP68 SERIES CONNECTION BOX WITH GEL		
JB6		IP68 CONNECTOR WITH GEL		
WCR275BLACK		H05RN-F CABLE 2x0.75mm² 1m		


 Recessed floor mounting only.


 Outdoor use.


 Dust-tight. Watertight (immersible).


 Protection against an impact energy of 20 Joules.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

 Hole cut to insert luminaire (55 mm)

 Product in conformity CE.

 Colour rendering index >80.

 LED specifications.
L70B10
70.000h

 Power supply not included.





Series connection.




Connect to a constant current Led power supply of 350mA DC.



Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.



7 years warranty.



Replaceable control gear by an electrician.