


MC010 S

This product contains 1 light source(s)



CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
MC010S27	SILVER	ALUMINIUM	DC 350mA 3V	1W	2700K	80 Lm	53 Lm
MC010S27W	SILVER	ALUMINIUM	DC 350mA 3V	1W	3000K	90 Lm	55 Lm

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
PLR35015	1-5W	AC 230V	DC 350mA	1	1	70°C	40°C
PLU35019	1-9W	AC 230V	DC 350mA	1	1	55°C	40°C
PSIP3509W	1-9W	AC 230V	DC 350mA	1	1	85°C	50°C
PSIP35018W	9-18W	AC 230V	DC 350mA	1	1	85°C	50°C



Wall mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Horizontal orientation maximum to 360°.



Hole cut to insert luminaire (20mm)



Beam 12°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.




Power supply not included.



Connect to a constant current Led power supply of 350mA DC.



7 years warranty.



Replaceable control gear by an electrician.