


MC020 S

This product contains 1 light source(s)



CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
MC020S27	SILVER	ALUMINIUM	DC 350mA 6V	2W	2700K	160 Lm	107 Lm	90

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
PLR35015	1-5W	AC 230V	DC 350mA	1	1	70°C	40°C
PLU35019	1-9W	AC 230V	DC 350mA	1	1	55°C	40°C
PSIP3509W	1-9W	AC 230V	DC 350mA	1	1	85°C	50°C
PSIP35018W	9-18W	AC 230V	DC 350mA	1	1	85°C	50°C



Wall mounting only. This lamp illuminates on 2 areas.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Horizontal orientation maximum to 360°.



Hole cut to insert luminaire (20mm)



Beam 12°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.




Power supply not included.



Connect to a constant current Led power supply of 350mA DC.



7 years warranty.



Replaceable control gear by an electrician.