


# MF02 IP

This product contains 1 light source(s)



CODE	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
MF02IP27	STAINLESS STEEL 316	DC 350mA 3V	1W	2700K	80 Lm	52 Lm
MF02IPNW	STAINLESS STEEL 316	DC 350mA 3V	1W	4000K	90 Lm	66 Lm

ACCESSOIRES	MATERIAL	DESCRIPTION	L (mm)
WBM01	STAINLESS STEEL 316	SINGLE ROUND BASE 45x10mm	
WBM02	STAINLESS STEEL 316	DOUBLE RECTANGULAR BASE 84x54x13mm	84

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
PLR35015	1-5W	AC 230V	DC 350mA	1	1	70°C	40°C
PLU35019	1-9W	AC 230V	DC 350mA	1	1	55°C	40°C
PSIP3509W	1-9W	AC 230V	DC 350mA	1	1	85°C	50°C
PSIP35018W	9-18W	AC 230V	DC 350mA	1	1	85°C	50°C



Wall mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Vertical orientation maximum to 45°.



Horizontal orientation maximum to 360°.



Beam 15°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Power supply not included.




Connect to a constant current Led power supply of 350mA DC.



Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.

**7** 7 years warranty.



Replaceable control gear by an electrician.