


# ML01

This product contains 8 light source(s)



| CODE   | COLOR  | MATERIAL            | DC          | LED | T° (K) | LED Lumen | System Lumen |
|--------|--------|---------------------|-------------|-----|--------|-----------|--------------|
| ML0127 | SILVER | STAINLESS STEEL 316 | DC 350mA 3V | 1W  | 2700K  | 80 Lm     | 4 Lm         |
| ML01WW | SILVER | STAINLESS STEEL 316 | DC 350mA 3V | 1W  | 3000K  | 90 Lm     | 4 Lm         |
| ML01NW | SILVER | STAINLESS STEEL 316 | DC 350mA 3V | 1W  | 4000K  | 90 Lm     | 4 Lm         |

| ACCESSOIRES | DESCRIPTION                | L (mm) |  |
|-------------|----------------------------|--------|--|
| PLR35015    | DRIVER 1-5W 350mA CC       | 53     |  |
| PLU35019    | DRIVER 1-9W 350mA CC       | 111    |  |
| PSIP3509W   | DRIVER 1-9W 350mA CC IP65  | 149    |  |
| PSIP35018W  | DRIVER 9-18W 350mA CC IP65 | 149    |  |



Recessed wall mounting only.



Indoor and outdoor use.



Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (126mm)



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Power supply not included.



Series connection.




Connect to a constant current Led power supply of 350mA DC.



Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.



7 years warranty.



Replaceable control gear by an electrician.