


ML02

This product contains 8 light source(s)



CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
ML0227	SILVER	STAINLESS STEEL 316	DC 350mA 3V	1W	2700K	80 Lm	23 Lm
ML02NW	SILVER	STAINLESS STEEL 316	DC 350mA 3V	1W	4000K	90 Lm	35 Lm

ACCESSOIRES	DESCRIPTION	L (mm)	
PLR35015	DRIVER 1-5W 350mA CC	53	
PLU35019	DRIVER 1-9W 350mA CC	111	
PSIP3509W	DRIVER 1-9W 350mA CC IP65	149	
PSIP35018W	DRIVER 9-18W 350mA CC IP65	149	



Recessed wall mounting only.



Indoor and outdoor use.



Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (126mm)



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Power supply not included.



Series connection.




Connect to a constant current Led power supply of 350mA DC.



Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.



7 years warranty.



Replaceable control gear by an electrician.