


SL030

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	System Lumen
SL13027	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	70 Lm (350mA) 120 Lm (700mA)
SL13030	BLACK	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	75 Lm (350mA) 135 Lm (700mA)
SL030F27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	70 Lm (350mA) 120 Lm (700mA)
SL030FWW	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	75 Lm (350mA) 135 Lm (700mA)
SL030FNW	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	4000K	95 Lm (350mA) 140 Lm (700mA)
SL130ZMBX27	BRONZE	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	2700K	70 Lm (350mA) 120 Lm (700mA)
SL130ZMBX30	BRONZE	ALUMINIUM	DC 350mA 3V DC 700mA 3V	1W (350mA) 2W (700mA)	3000K	75 Lm (350mA) 135 Lm (700mA)



BLACK



STAINLESS STEEL 316



BRONZE

ACCESSOIRES	DESCRIPTION	L (mm)	
PSIP3509W	DRIVER 1-9W 350mA CC IP65	149	
PSIP35018W	DRIVER 9-18W 350mA CC IP65	149	
PSIP70018W	DRIVER 2-18W 700mA CC IP65	149	
PSIP70036W	DRIVER 18-36W 700mA CC IP65	162	
JB2	IP68 3-OUTLET SERIES JUNCTION BOX		
JB4	IP68 SERIES CONNECTION BOX WITH GEL		
JB6	IP68 CONNECTOR WITH GEL		
WCR275BLACK	H05RN-F CABLE 2x0.75mm² 1m		

Ground mounting only.

Outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Vertical orientation maximum to 90°.



Beam 25°.



Colour rendering index >80.



Product in conformity CE.



LED specifications.



Power supply not included.



Series connection.




Connect to a constant current Led power supply of 350mA DC.



Connect to a constant current Led power supply of 700mA DC.



7 years warranty.



Replaceable control gear by an electrician.