


# SL040A

This product contains 3 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	System Lumen	α
SL040AS27	BLACK	ALUMINIUM	DC 700mA 9V	7W	2700K	377 Lm	18°
SL040ASWW	BLACK	ALUMINIUM	DC 700mA 9V	7W	3000K	413 Lm	18°
SL040AF27	BLACK	ALUMINIUM	DC 700mA 9V	7W	2700K	377 Lm	38°
SL040AFWW	BLACK	ALUMINIUM	DC 700mA 9V	7W	3000K	413 Lm	38°

ACCESSOIRES	DESCRIPTION	L (mm)	
PSIP70018W	DRIVER 2-18W 700mA CC IP65	149	
PSIP70036W	DRIVER 18-36W 700mA CC IP65	162	
JB2	IP68 3-OUTLET SERIES JUNCTION BOX		
JB4	IP68 SERIES CONNECTION BOX WITH GEL		
JB6	IP68 CONNECTOR WITH GEL		
WCR275BLACK	H05RN-F CABLE 2x0.75mm² 1m		



Ground mounting only.



Outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Vertical orientation maximum to 90°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Power supply not included.




Series connection.

700  
mA

Connect to a constant current Led power supply of 700mA DC.

7

7 years warranty.



Replaceable control gear by an electrician.