


SL220

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	System Lumen	α
SL220BNBX27	BLACK	ALUMINIUM	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	310 Lm (350mA) 530 Lm (700mA)	12°
SL220BNBX30	BLACK	ALUMINIUM	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	3000K	310 Lm (350mA) 530 Lm (700mA)	12°
SL220BWBX27	BLACK	ALUMINIUM	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	290 Lm (350mA) 515 Lm (700mA)	40°
SL220BWBX30	BLACK	ALUMINIUM	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	3000K	300 Lm (350mA) 520 Lm (700mA)	40°
SL220DWBX27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	290 Lm (350mA) 515 Lm (700mA)	40°
SL220DWBX30	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	3000K	300 Lm (350mA) 520 Lm (700mA)	40°
SL220ZWBX27	BRONZE	ALUMINIUM	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	290 Lm (350mA) 515 Lm (700mA)	40°
SL220ZWBX30	BRONZE	ALUMINIUM	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	3000K	300 Lm (350mA) 520 Lm (700mA)	40°
SL220CWBX27	COPPER	COPPER	DC 350mA 6,5V DC 700mA 6,5V	2,2W (350mA) 4,6W (700mA)	2700K	290 Lm (350mA) 515 Lm (700mA)	40°



BLACK











STAINLESS STEEL 316









BRONZE





COPPER


ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	L (mm)
GH220B	BLACK	ALUMINIUM	ASYMMETRICAL CYLINDER	
GH220D	STAINLESS STEEL 316	STAINLESS STEEL 316	ASYMMETRICAL CYLINDER	
GH220Z	BRONZE	ALUMINIUM	ASYMMETRICAL CYLINDER	
GS220B	BLACK	ALUMINIUM	LOW-GLARE CYLINDER	
GS220D	STAINLESS STEEL 316	STAINLESS STEEL 316	LOW-GLARE CYLINDER	
GS220Z	BRONZE	ALUMINIUM	LOW-GLARE CYLINDER	
PSIP3509W			DRIVER 1-9W 350mA CC IP65	149 
PSIP35018W			DRIVER 9-18W 350mA CC IP65	149 


ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	L (mm)	
PSIP70018W			DRIVER 2-18W 700mA CC IP65	149	
PSIP70036W			DRIVER 18-36W 700mA CC IP65	162	
JB2			IP68 3-OUTLET SERIES JUNCTION BOX		
JB4			IP68 SERIES CONNECTION BOX WITH GEL		
JB6			IP68 CONNECTOR WITH GEL		


 Ground mounting only.


 Outdoor use.


 Protected against the ingress of dust. Protected against jets of water.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.


 Vertical orientation maximum to 90°.


 Product in conformity CE.


 Colour rendering index >80.


 LED specifications.


 Power supply not included.

 Series connection.

 Connect to a constant current Led power supply of 350mA DC.

 Connect to a constant current Led power supply of 700mA DC.

 7 years warranty.

 Replaceable control gear by an electrician.