


TIBLI R-B

- Fixed round recessed spotlight.
 - Fastened with louvers.
 - Quick connector and 2.00m cable included.
 - Dimmable converter 350mA (remote mounting) to be ordered separately (CD167 min. 2S max. 4W, compatible with start and end-of-phase dimmer).
- This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO468WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 350mA 3V	1,2W	3000K	115 Lm	106 Lm
DO468WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 350mA 3V	1,2W	3000K	115 Lm	106 Lm



MATT BLACK

MATT WHITE

ACCESSOIRES **DESCRIPTION**

CD167	DRIVER 2-4W 350mA CC DIM	
-------	--------------------------	---



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,70 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (25 mm)



Beam 20°.



Product in conformity CE.



Colour rendering index >80.



UGR below 19.



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Power supply not included.



Series connection.




Connect to a constant current Led power supply of 350mA DC.



5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.