






UL010

This product contains 1 light source(s) of energy efficiency F.



CODE	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
UL01027	STAINLESS STEEL 316	DC 700mA 3V	3W	2700K	240 Lm	92 Lm
UL010WW	STAINLESS STEEL 316	DC 700mA 3V	3W	3000K	250 Lm	95 Lm
UL010NW	STAINLESS STEEL 316	DC 700mA 3V	3W	4000K	260 Lm	119 Lm
UL010A27	BRASS	DC 700mA 3V	3W	2700K	240 Lm	92 Lm
UL010AWW	BRASS	DC 700mA 3V	3W	3000K	250 Lm	95 Lm



ACCESSOIRES	DESCRIPTION	
JB2	IP68 3-OUTLET SERIES JUNCTION BOX	
JB4	IP68 SERIES CONNECTION BOX WITH GEL	
JB6	IP68 CONNECTOR WITH GEL	
WCR275BLACK	H05RN-F CABLE 2x0.75mm² 1m	

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
PSIP70018W	2-18W	AC 230V	DC 700mA	1	1	85°C	50°C
PSIP70036W	18-36W	AC 230V	DC 700mA	1	1	85°C	50°C



Wall and ceiling mounting only.



Ground mounting only.



Outdoor use.



Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Vertical orientation maximum to 360°.



Horizontal orientation maximum to 360°.



Beam 25°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.




Power supply not included.



Connect to a constant current Led power supply of 700mA DC.



7 years warranty.



Replaceable control gear by an electrician.