


















# UL030 RGBW


This product contains 4 light source(s)



CODE	MATERIAL	DC	LED	T° (K)	System Lumen	L (mm)
UL030RGBW	STAINLESS STEEL 316	DC 350mA	4x3W	RGB+W (4000K)	177 Lm (4000K)	65

ACCESSOIRES	DESCRIPTION	
C100924	LED CONTROLLER RGB(W)	
PR3011	RGB(W) POWER REPEATER 350mA 4x8,4W	
JB7	IP68 5-POLE SCREW CONNECTOR	
CR575RGBW	PVC CABLE 5x0,75mm² RGBW 1m	

-  Wall and ceiling mounting only.
-  Ground mounting only.
-  Outdoor use.
-  IP67 Dust-tight. Watertight (immersible).
-  Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.
-  Vertical orientation maximum to 360°.
-  Horizontal orientation maximum to 360°.
-  Beam 45°.
-  Product in conformity CE.
-  RGB + White.
-  LED specifications.
-  Power supply not included.
-  Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.
-  5 years warranty.



Replaceable control gear by an electrician.