


# UL030

This product contains 1 light source(s) of energy efficiency E.



of energy efficiency F.  
of energy efficiency E.

CODE	COLOR	MATERIAL	DC	LED	T° (K)	System Lumen	α
UL030DNBX27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 700mA 6,5V	4,6W	2700K	470 Lm	12°
UL030DNBX30	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 700mA 6,5V	4,6W	3000K	480 Lm	12°
UL030DNBX40	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 700mA 6,5V	4,6W	4000K	490 Lm	12°
UL030ANAX27	BRASS	BRASS	DC 700mA 6,5V	4,6W	2700K	470 Lm	12°
UL030ANAX30	BRASS	BRASS	DC 700mA 6,5V	4,6W	3000K	480 Lm	12°
UL030DWBX27	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 700mA 6,5V	4,6W	2700K	470 Lm	40°
UL030DWBX30	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 700mA 6,5V	4,6W	3000K	480 Lm	40°
UL030DWBX40	STAINLESS STEEL 316	STAINLESS STEEL 316	DC 700mA 6,5V	4,6W	4000K	490 Lm	40°
UL030BWBX27	BLACK	ALUMINIUM	DC 700mA 6,5V	4,6W	2700K	470 Lm	40°
UL030BWBX30	BLACK	ALUMINIUM	DC 700mA 6,5V	4,6W	3000K	480 Lm	40°
UL030AWAX27	BRASS	BRASS	DC 700mA 6,5V	4,6W	2700K	470 Lm	40°
UL030AWAX30	BRASS	BRASS	DC 700mA 6,5V	4,6W	3000K	480 Lm	40°







STAINLESS STEEL 316



BRASS




BLACK

ACCESSOIRES	DESCRIPTION	
JB2	IP68 3-OUTLET SERIES JUNCTION BOX	
JB4	IP68 SERIES CONNECTION BOX WITH GEL	
JB6	IP68 CONNECTOR WITH GEL	
WCR275BLACK	H05RN-F CABLE 2x0.75mm² 1m	

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
PSIP70018W	2-18W	AC 230V	DC 700mA	1	1	85°C	50°C
PSIP70036W	18-36W	AC 230V	DC 700mA	1	1	85°C	50°C

 Wall and ceiling mounting only.

 Ground mounting only.

 Outdoor use.



Totally protected against dust, Protected against prolonged effect of immersion under pressure (2m).



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Vertical orientation maximum to 360°.



Horizontal orientation maximum to 360°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.




Power supply not included.



Connect to a constant current Led power supply of 700mA DC.



7 years warranty.



Replaceable control gear by an electrician.