



ULCARGB

This product contains 12 light source(s)



CODE	COLOR	MATERIAL	DC	LED	T° (K)	System Lumen	α	L (mm)
UL345CARGB	BLACK	ALUMINIUM	DC 350mA	3x4W	RGB	51 - 161 Lm	110°	400
UL346CARGB	BLACK	ALUMINIUM	DC 350mA	3x4W	RGB	23 - 136 Lm	25x6°	400
UL347CARGB	BLACK	ALUMINIUM	DC 350mA	3x4W	RGB	51 - 285 Lm	45°	400



BLACK



BLACK



BLACK

ACCESSOIRES	DESCRIPTION	
C100924	LED CONTROLLER RGB(W)	
PR3011	RGB(W) POWER REPEATER 350mA 4x8,4W	
JB3	IP66 7-OUTLET PARALLEL JUNCTION BOX	



Wall and ceiling mounting only.



Floor surface mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Vertical orientation maximum to 180°.



Product in conformity CE.



Colour change RGB.



LED specifications.



Power supply not included.



Connect to a constant current Led power supply of 350mA DC.

5 5 years warranty.