


WL220 MAINS

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	System Lumen
WL220BWB27	BLACK	ALUMINIUM	AC 230V	DC 350mA	5,7W	2700K	515 Lm
WL220BWB30	BLACK	ALUMINIUM	AC 230V		5,7W	3000K	520 Lm
WL220DWB27	STAINLESS STEEL 316	STAINLESS STEEL 316	AC 230V		5,7W	2700K	515 Lm
WL220DWB30	STAINLESS STEEL 316	STAINLESS STEEL 316	AC 230V		5,7W	3000K	520 Lm
WL220ZWB27	BRONZE	ALUMINIUM	AC 230V		5,7W	2700K	515 Lm
WL220ZWB30	BRONZE	ALUMINIUM	AC 230V		5,7W	3000K	520 Lm
WL220CWB27	COPPER	COPPER	AC 230V		5,7W	2700K	515 Lm



BLACK



STAINLESS STEEL 316



BRONZE



COPPER

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	
GH220B	BLACK	ALUMINIUM	ASYMMETRICAL CYLINDER	
GH220D	STAINLESS STEEL 316	STAINLESS STEEL 316	ASYMMETRICAL CYLINDER	
GH220Z	BRONZE	ALUMINIUM	ASYMMETRICAL CYLINDER	
GS220B	BLACK	ALUMINIUM	LOW-GLARE CYLINDER	
GS220D	STAINLESS STEEL 316	STAINLESS STEEL 316	LOW-GLARE CYLINDER	
GS220Z	BRONZE	ALUMINIUM	LOW-GLARE CYLINDER	



Wall and ceiling mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 330°.



Beam 40°.



Product in conformity CE.



Colour rendering index >80.




LED specifications.




Power supply included.



7 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.