


WL340

This product contains 1 light source(s) of energy efficiency F.



| CODE | COLOR | MATERIAL | AC | LED | T° (K) | LED Lumen | System Lumen |
|-----------|----------------------|---------------------|---------|------|--------|-----------|--------------|
| WL339WW | CAST STAINLESS STEEL | STAINLESS STEEL 316 | AC 230V | 2,6W | 3000K | 205 Lm | 50 Lm |
| WL340WW | BRUSHED BRASS | STAINLESS STEEL 316 | AC 230V | 2,6W | 3000K | 205 Lm | 50 Lm |
| WL340AB27 | ANTIQUÉ BRASS | ANTIQUÉ BRASS | AC 230V | 2,6W | 2700K | 155 Lm | 49 Lm |
| WL340ABWW | ANTIQUÉ BRASS | ANTIQUÉ BRASS | AC 230V | 2,6W | 3000K | 205 Lm | 50 Lm |



CAST STAINLESS STEEL



BRUSHED BRASS



ANTIQUÉ BRASS

ACCESSOIRES DESCRIPTION

JB5 IP68 PARALLEL CONNECTION BOX WITH GEL



WC59 IP68 CONNECTOR



Recessed wall mounting only.



Recessed floor mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Earth wire . Fixture equipped with primary insulation only.



Hole cut to insert luminaire. (80mm)



Hole cut to insert recessed housing. (85mm).



Beam 50°.



Product in conformity CE.



Colour rendering index >80.




LED specifications.




Power supply included.



7 7 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.