



ABY 1 RD

- Fixed round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO461WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 15V	6,5W	3000K	550 Lm	519 Lm
DO461WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 15V	6,5W	3000K	550 Lm	519 Lm
DO461NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 15V	6,5W	4000K	800 Lm	600 Lm
DO461NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 15V	6,5W	4000K	800 Lm	600 Lm



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Beam 36°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 350mA DC.



The product is dimmable.




5 years warranty.






Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.