


ABY 3 RD

- Fixed round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO464WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1300 Lm	1151 Lm
DO464WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1300 Lm	1151 Lm
DO464NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1700 Lm	1447 Lm
DO464NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1700 Lm	1447 Lm



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (92mm)



Beam 45°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 350mA DC.



The product is dimmable.




5 years warranty.






Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.