


ADA 1 RX

- Adjustable round recessed spotlight.
- Fastened with springs.
- Remote non dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
OU49805	MATT BLACK	ALUMINIUM	AC 230V	DC 250mA 36V	9W	2700-3000-4000K	1100 Lm (4000K)	775 Lm (4000K)
OU49830	MATT WHITE	ALUMINIUM	AC 230V	DC 250mA 36V	9W	2700-3000-4000K	1100 Lm (4000K)	775 Lm (4000K)



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (78mm)



Minimum ceiling height to insert luminaire. (110mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 38°.



Product in conformity CE.



CRI > 90



LED specifications.



3 CCT.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Power supply included.

250
mA


Connect to a constant current Led power supply of 250mA DC.

3


3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.