


# ADA 2 RX

- Adjustable round recessed spotlight.
  - 2700K, 3000K or 4000K as desired via a switch at the back of the luminaire.
  - Fastened with springs.
  - Remote non dimmable converter supplied.
- This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
OU49905	MATT BLACK	ALUMINIUM	AC 230V	DC 500mA 36V	18W	2700-3000-4000K	2225 Lm (4000K)	1585 Lm (4000K)
OU49930	MATT WHITE	ALUMINIUM	AC 230V	DC 500mA 36V	18W	2700-3000-4000K	2225 Lm (4000K)	1585 Lm (4000K)



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire. (120mm)



Minimum ceiling height to insert luminaire. (145mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 38°.



Product in conformity CE.



CRI >90



LED specifications.



3 CCT.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Power supply included.

500  
mA


Connect to a constant current Led power supply of 500mA DC.

3


3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.