


# AL1014 RDX-230 B



| CODE      | COLOR               | MATERIAL       | AC      | LED  | T° (K) | LED Lumen | System Lumen |
|-----------|---------------------|----------------|---------|------|--------|-----------|--------------|
| DO236WW05 | MATT BLACK          | CAST ALUMINIUM | AC 230V | 7,5W | 3000K  | 700 Lm    | 640 Lm       |
| DO236WW30 | MATT WHITE          | CAST ALUMINIUM | AC 230V | 7,5W | 3000K  | 700 Lm    | 640 Lm       |
| DO236WW38 | ANODIZED ANTHRACITE | CAST ALUMINIUM | AC 230V | 7,5W | 3000K  | 700 Lm    | 640 Lm       |
| DO236WW39 | TITANIUM            | CAST ALUMINIUM | AC 230V | 7,5W | 3000K  | 700 Lm    | 640 Lm       |



NOIR MAT



BLANC MAT



ANTHRACITE ANODISE



TITANE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (68mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 38°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Luminaire with a 230V LED module.




The product is dimmable.



3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable LED light source by an electrician.