


AL1014 RDX



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen	α
DO16039	TITANIUM	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	940 Lm	830 Lm	38°
DO16105	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	990 Lm	870 Lm	38°
DO16125	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	990 Lm	870 Lm	38°
DO16130	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	990 Lm	870 Lm	38°
DO30225	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	940 Lm	800 Lm	60°
DO30230	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	940 Lm	800 Lm	60°
DO30238	ANODIZED ANTHRACITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	940 Lm	800 Lm	60°
DO30325	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	1000 Lm	850 Lm	60°
DO30330	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	1000 Lm	850 Lm	60°
DO30338	ANODIZED ANTHRACITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	1000 Lm	850 Lm	60°



TITANE

ANTHRACITE ANODISE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Minimum ceiling height to insert luminaire. (60mm)



Vertical orientation maximum to 20°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.





Class II power supply included.



Connect to a constant current Led power supply of 500mA DC.




The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.