


# AL1014 RDX OUT



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
OU327WW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	940 Lm	827 Lm
OU327WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	940 Lm	827 Lm
OU327NW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	990 Lm	869 Lm
OU327NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	990 Lm	869 Lm



ANTHRACITE



BLANC MAT



Recessed ceiling mounting only.



Outdoor use.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Vertical orientation maximum to 20°.



Beam 38°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.




Connect to a constant current Led power supply of 500mA DC.





The product is dimmable.



**5** 5 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable LED light source by an electrician.

 Replaceable control gear by an electrician.