


AL1014 RX

- Adjustable round recessed spotlight.
- Fastened with springs.
- Can be covered with peeled insulation.
- Automatic double terminal block.
- Remote non dimmable converter supplied.
- Ring covering a drilling diameter of 90 to 120mm to be ordered separately.
- Optional dimmable converter CD102 to be ordered separately.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
AL101425	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	3000K	760 Lm	655 Lm
AL101430	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	3000K	760 Lm	655 Lm
DO11525	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	4000K	820 Lm	705 Lm
DO11530	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	4000K	820 Lm	705 Lm



ALUMINIUM



MATT WHITE

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	L (mm)
DO33330	MATT WHITE	ALUMINIUM	RING FOR CUTTING HOLE 90-120mm	178



CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD102	6,5-13,5W	AC 230V	DC 350mA	1	1	85°C	55°C



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Vertical orientation maximum to 20°.



Beam 38°.



Product in conformity CE.



CRI>80




LED specifications.




Photobiological risk RG1




650° Test on 650°.


 Product can be covered after installation with insulation. (not blown)


 Class II power supply included.

350 mA Connect to a constant current Led power supply of 350mA DC.

5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable LED light source by an electrician.

 Replaceable control gear by an electrician.