


AL1014 SDX



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO16225	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	900 Lm	785 Lm
DO16230	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	900 Lm	785 Lm
DO16325	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	940 Lm	825 Lm
DO16330	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	940 Lm	825 Lm



ALUMINIUM

BLANC MAT



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Minimum ceiling height to insert luminaire. (60mm)



Vertical orientation maximum to 20°.



Beam 38°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 500mA DC.






The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.