


AL3012 RD

- Fixed round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO17105	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	1050 Lm	820 Lm
DO17130	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	1050 Lm	867 Lm
DO17144	MATT WHITE - GOLD	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	1050 Lm	867 Lm



MATT BLACK



MATT WHITE



MATT WHITE - GOLD



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (75mm)



Beam 38°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 500mA DC.



The product is dimmable.




5 years warranty.






Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.