


AL3012 RD WARM

- Fixed round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Can be covered with peeled insulation.
- Variable colour temperature from 1800K to 3000K depending on dimming intensity.
- Remote dimmable converter supplied.
- Compatible with start and end-phase dimmer.



This product contains 1 light source(s) of energy efficiency F.

CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO33005	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	1800-3000K	530 Lm (3000K)	405 Lm (3000K)
DO33030	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	1800-3000K	530 Lm (3000K)	425 Lm (3000K)



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (75mm)



Beam 38°.



Product in conformity CE.



CRI >90



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Class II power supply included.



Connect to a constant current Led power supply of 350mA DC.



Dim to warm from 1800K to 3000K.




5 years warranty.




Photometric data available on our website: www.indigo-lighting.com





Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.