


# ALEX RDX

RE  
2020



- 4 in 1 adjustable round recessed spotlight.
- 2700K, 3000K, 4000K or 65000K as desired via a switch on the converter. .
- Fastened with springs.
- Can be covered with peeled or blown insulation, converter included.
- Automatic double terminal block.
- Remote dimmable converter supplied.
- Compatible with start and end-ofphase dimmer.
- Replacement spotlight or driver available separately.



This product contains 1 light source(s) of energy efficiency E.

CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO53305	MATT BLACK	ALU.+COMPOSITE	AC 230V	DC 260mA 18V	6W	2700-3000-4000-6500K	700 Lm (4000K)	575 Lm (4000K)
DO53321	SATIN NICKEL	ALU.+COMPOSITE	AC 230V	DC 260mA 18V	6W	2700-3000-4000-6500K	700 Lm (4000K)	575 Lm (4000K)
DO53330	MATT WHITE	ALU.+COMPOSITE	AC 230V	DC 260mA 18V	6W	2700-3000-4000-6500K	700 Lm (4000K)	575 Lm (4000K)



MATT BLACK



SATIN NICKEL



MATT WHITE

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION
LP53305	MATT BLACK	ALU.+COMPOSITE	SPOT 6W 700Lm 60° IP65
LP53321	SATIN NICKEL	ALU.+COMPOSITE	SPOT 6W 700Lm 60° IP65
LP53330	MATT WHITE	ALU.+COMPOSITE	SPOT 6W 700Lm 60° IP65
CD533			DRIVER 6W 260mA CC DIM



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Minimum ceiling height to insert luminaire. (40mm)



Vertical orientation maximum to 25°.



Beam 60°.



Product in conformity CE.



**CRI**  
**>80**

CRI>80

**2700K**  
**3000K**  
**4000K**  
**6500K**

4 CCT.

**LED**  
**L80B20**  
**50.000h**

LED specifications.

**RG1**

Photobiological risk RG1

**RE**  
**2020**

In compliance with current thermal regulation. (France)

**850°**

Test on 850°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)



Class II power supply included.

**260**  
**mA**

Connect to a constant current Led power supply of 260mA DC.




The product is dimmable.

**5**

5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an end-user.



Non-replaceable light source.