


# ALIS 1014 RDX

- Adjustable round recessed spotlight.
- Fastened with springs.
- Automatic double terminal block.
- With membrane to keep it watertight .
- Remote dimmable converter supplied. .
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency E.



**RE**  
**2020**



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO227WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	3000K	740 Lm	675 Lm
DO227WW25	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	3000K	740 Lm	675 Lm
DO227WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	3000K	740 Lm	675 Lm
DO227NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	4000K	800 Lm	730 Lm
DO227NW25	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 18V	6W	4000K	800 Lm	730 Lm
DO227NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 18V	6W	4000K	800 Lm	730 Lm



MATT BLACK



ALUMINIUM



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 0,50 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 38°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation. (France)



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.



**350  
mA**

Connect to a constant current Led power supply of 350mA DC.




The product is dimmable.

**5**


5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.