


APA RD-230

- Round floor recessed fixture.
- Carriage resistance 1500kg.
- With removable honeycomb grid.
- Recessed box and 1.00m cable supplied.
- Dimmable.

This product contains 1 light source(s) of energy efficiency G.



CODE	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
OU326WW16	STAINLESS STEEL 316	AC 230V	8W	3000K	550 Lm	352 Lm
OU326NW16	STAINLESS STEEL 316	AC 230V	8W	4000K	600 Lm	407 Lm



Recessed floor mounting only.



Indoor and outdoor use.



Dust-tight. Watertight (immersible).



Protection against an impact energy of 5 Joules.



Earth wire . Fixture equipped with primary insulation only.



Hole cut to insert luminaire (92mm)



Hole cut to insert recessed housing. (97mm).



Beam 60°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Luminaire with a 230V LED module.



The product is dimmable.




Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.