


ARRAS


- Linear structure for 48V track.
- Non dimmable.


This product contains 1 light source(s) of energy efficiency F.





CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
TR376WW05	MATT BLACK	ALUMINIUM	DC 48V	26W	3000K	3330 Lm	1249 Lm	1201
TR377WW05	MATT BLACK	ALUMINIUM	DC 48V	35W	3000K	4330 Lm	1632 Lm	1599

 Ceiling mounting only.


 Indoor use only.

 **IP 20** Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.


 **IK 02** Protection against an impact energy of 0,20 Joule.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.


 **110°** Beam 110°.


 **CE** Product in conformity CE.


 **CRI >80** CRI>80


 **LED** L70B50 50.000h LED specifications.


 **RG1** Photobiological risk RG1

 **650°** Test on 650°.

 **48V DC** Connect to a constant voltage LED power supply of 48VDC.

 **3** 3 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable LED light source by an electrician.

