


AUREA 1 C

- Adjustable round wall or ceiling lamp.
- 2700K, 3000K or 4000K as desired via a switch at the back of the luminaire.
- Dimmable converter built in the device.
- Compatible with start-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA25605	MATT BLACK	ALUMINIUM	AC 230V	6W	2700-3000-4000K	715 Lm (4000K)	550 Lm (4000K)
WA25608	MATT BLACK - CHAMPAGNE	ALUMINIUM	AC 230V	6W	2700-3000-4000K	715 Lm (4000K)	550 Lm (4000K)
WA25683	MATT BLACK - ROSE	ALUMINIUM	AC 230V	6W	2700-3000-4000K	715 Lm (4000K)	550 Lm (4000K)
WA25630	MATT WHITE	ALUMINIUM	AC 230V	6W	2700-3000-4000K	715 Lm (4000K)	550 Lm (4000K)
WA25649	MATT WHITE - CHAMPAGNE	ALUMINIUM	AC 230V	6W	2700-3000-4000K	715 Lm (4000K)	550 Lm (4000K)
WA25682	MATT WHITE - ROSE	ALUMINIUM	AC 230V	6W	2700-3000-4000K	715 Lm (4000K)	550 Lm (4000K)



MATT BLACK



MATT BLACK - CHAMPAGNE



MATT BLACK - ROSE



MATT WHITE



MATT WHITE - CHAMPAGNE



MATT WHITE - ROSE



Wall and ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 38°.



Product in conformity CE.



CRI>90



3 CCT.



LED specifications.



Photobiological risk RG1



Test on 850°.



Power supply included.




The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.