TECHNICAL DATA INDOOR WALL LIGHTS




AUREA 1 W

- Decorative wall lamp.
- Exposed base with dimmer swith and plug USB (5VDC, 2, 4A). - 2700K, 3000K or 4000K as desired via a
- switch at the back of the luminaire.
- Dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency G.





CODE	COLOR	MATERIAL	AC	LED	Т° (К)	LED Lumen	System Lumen
WA25805	MATT BLACK	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25808	MATT BLACK - CHAMPAGNE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25883	MATT BLACK - ROSE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25830	MATT WHITE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25849	MATT WHITE - CHAMPAGNE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25882	MATT WHITE - ROSE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)











MATT BLACK

MATT BLACK -CHAMPAGNE

MATT WHITE

MATT BLACK - ROSE

MATT WHITE -CHAMPAGNE

MATT WHITE - ROSE

Wall mounting only.
Indoor use only.
$\fbox{Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.}$
IK Protection against an impact energy of 0,20 Joule.
\square Earth wire . Fixture equipped with primary insulation only.
yertical orientation maximum to 90°.
Horizontal orientation maximum to 350°.
Beam 38°. 38°
CE Product in conformity CE.
CRI >90
2700 K 3000 K 4000 K
LED Specifications.
RG1 Photobiological risk RG1
850° Test on 850°.
Power supply included.

TECHNICAL DATA

INDOOR

WALL LIGHTS

With dimmer switch.

USB

0

5

5 years warranty.

With USB plug.

Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.

è : :

Replaceable LED light source by an electrician.

