


AUREA 2 C
















- Adjustable wall or ceiling lamp.
- 2700K, 3000K or 4000K as desired with a switch at the back the luminaire.
- Dimmable converter built in the device.
- Compatible with start-of-phase dimmer.

This product contains 2 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA25705	MATT BLACK	ALUMINIUM	AC 230V	2x6W	2700-3000-4000K	2x715 Lm (4000K)	2x550 Lm (4000K)
WA25708	MATT BLACK - CHAMPAGNE	ALUMINIUM	AC 230V	2x6W	2700-3000-4000K	2x715 Lm (4000K)	2x550 Lm (4000K)
WA25783	MATT BLACK - ROSE	ALUMINIUM	AC 230V	2x6W	2700-3000-4000K	2x715 Lm (4000K)	2x550 Lm (4000K)
WA25730	MATT WHITE	ALUMINIUM	AC 230V	2x6W	2700-3000-4000K	2x715 Lm (4000K)	2x550 Lm (4000K)
WA25749	MATT WHITE - CHAMPAGNE	ALUMINIUM	AC 230V	2x6W	2700-3000-4000K	2x715 Lm (4000K)	2x550 Lm (4000K)
WA25782	MATT WHITE - ROSE	ALUMINIUM	AC 230V	2x6W	2700-3000-4000K	2x715 Lm (4000K)	2x550 Lm (4000K)



-  Wall and ceiling mounting only.
-  Indoor use only.
-  IP 44 Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.
-  IK 02 Protection against an impact energy of 0,20 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 350°.
-  Beam 38°.
-  Product in conformity CE.
-  CRI >90
-  3 CCT.
-  LED specifications.
-  Photobiological risk RG1
-  Test on 850°.
-  Power supply included.




The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.