

# AUREA 2 W

- Decorative wall lamp.
- Exposed base with dimmer switch and USB socket (5VDC, 2,4A).
- Hose length 250mm.
- 2700K, 3000K or 4000K as desired via a switch at the back of the luminaire.
- Dimmable converter built in the device.



This product contains 1 light source(s) of energy efficiency G.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA25905	MATT BLACK	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25908	MATT BLACK - CHAMPAGNE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25983	MATT BLACK - ROSE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25930	MATT WHITE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25949	MATT WHITE - CHAMPAGNE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)
WA25982	MATT WHITE - ROSE	ALUMINIUM	AC 230V	7W	2700-3000-4000K	625 Lm (4000K)	500 Lm (4000K)



- Wall mounting only.
- Indoor use only.
- Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
- Protection against an impact energy of 0,20 Joule.
- Earth wire . Fixture equipped with primary insulation only.
- Horizontal orientation maximum to 350°.
- Beam 38°.
- Product in conformity CE.
- CRI>90
- 3 CCT.
- LED specifications.
- Photobiological risk RG1
- Test on 850°.
- Power supply included.
- With dimmer switch.




With USB plug.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.