



BERN


- Linear structure for accent lighting for 48V track.
- Low luminance reflector.


This product contains 1 light source(s) of energy efficiency F.





CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	α	L (mm)
NOT DIMMABLE									
TR281SW05	MATT BLACK	ALUMINIUM	DC 48V	12W	2700K	1000 Lm	802 Lm	12°	205
TR281WW05	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	832 Lm	12°	205
TR281NW05	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	878 Lm	12°	205
TR280SW05	MATT BLACK	ALUMINIUM	DC 48V	12W	2700K	1000 Lm	831 Lm	24°	205
TR280WW05	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	865 Lm	24°	205
TR280NW05	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	941 Lm	24°	205
TR279SW05	MATT BLACK	ALUMINIUM	DC 48V	12W	2700K	1000 Lm	816 Lm	36°	205
TR279WW05	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	849 Lm	36°	205
TR279NW05	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	939 Lm	36°	205
TR378WW05	MATT BLACK	ALUMINIUM	DC 48V	21W	3000K	1850 Lm	1475 Lm	12°	407
TR379WW05	MATT BLACK	ALUMINIUM	DC 48V	21W	3000K	1850 Lm	1512 Lm	24°	407
TR380WW05	MATT BLACK	ALUMINIUM	DC 48V	21W	3000K	1850 Lm	1510 Lm	36°	407
TR381WW05	MATT BLACK	ALUMINIUM	DC 48V	39W	3000K	3710 Lm	3006 Lm	12°	812
TR382WW05	MATT BLACK	ALUMINIUM	DC 48V	39W	3000K	3710 Lm	3021 Lm	24°	812
TR383WW05	MATT BLACK	ALUMINIUM	DC 48V	39W	3000K	3710 Lm	3041 Lm	36°	812
DALI DIMMABLE									
TR281WW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	832 Lm	12°	205
TR281NW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	878 Lm	12°	205
TR280WW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	865 Lm	24°	205
TR280NW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	941 Lm	24°	205
TR279WW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	849 Lm	36°	205
TR279NW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	939 Lm	36°	205
TR378WW05DA	MATT BLACK	ALUMINIUM	DC 48V	21W	3000K	1850 Lm	1475 Lm	12°	407
TR379WW05DA	MATT BLACK	ALUMINIUM	DC 48V	21W	3000K	1850 Lm	1512 Lm	24°	407
TR380WW05DA	MATT BLACK	ALUMINIUM	DC 48V	21W	3000K	1850 Lm	1510 Lm	36°	407
TR381WW05DA	MATT BLACK	ALUMINIUM	DC 48V	26W	3000K	2200 Lm	1745 Lm	12°	812
TR382WW05DA	MATT BLACK	ALUMINIUM	DC 48V	26W	3000K	2200 Lm	1803 Lm	24°	812
TR383WW05DA	MATT BLACK	ALUMINIUM	DC 48V	26W	3000K	2200 Lm	1772 Lm	36°	812


 Ceiling mounting only.

 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.

 Protection against an impact energy of 0,20 Joule.

 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

 Product in conformity CE.



CRI
>80

CRI>80

LED
L70B50
50,000h

LED specifications.

UGR
<19

UGR below 19.

RG1

Photobiological risk RG1

650°


Test on 650°.


48V
DC

Connect to a constant voltage LED power supply of 48VDC.

3

3 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable LED light source by an electrician.