


BORA RD-230 EVO

RE
2020



- 4 in 1 fixed round recessed spotlight.
- 2700K, 3000K, 4000K or 6000K selectable via a switch at the back of the luminaire.
- Fastened with springs.
- Can be covered with peeled or blown insulation.
- Automatic double terminal block.
- Dimmable, compatible with end-of-phase dimmer.
- Replacement source or driver available separately.



This product contains 1 light source(s) of energy efficiency E.

| CODE | COLOR | MATERIAL | AC | LED | T° (K) | LED Lumen | System Lumen |
|---------|--------------|----------------|---------|-----|----------------------|----------------|----------------|
| DO52005 | MATT BLACK | ALU.+COMPOSITE | AC 230V | 5W | 2700-3000-4000-6000K | 615 Lm (4000K) | 545 Lm (4000K) |
| DO52021 | SATIN NICKEL | ALU.+COMPOSITE | AC 230V | 5W | 2700-3000-4000-6000K | 615 Lm (4000K) | 545 Lm (4000K) |
| DO52030 | MATT WHITE | ALU.+COMPOSITE | AC 230V | 5W | 2700-3000-4000-6000K | 615 Lm (4000K) | 545 Lm (4000K) |



MATT BLACK



SATIN NICKEL



MATT WHITE

| ACCESSOIRES | DESCRIPTION | |
|-------------|---------------------------|--|
| LP520 | LED SOURCE 3,8W 615Lm 60° | |
| CD520 | DRIVER 5W 180mA CC DIM | |



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (68mm)



Beam 60°.



Product in conformity CE.



Colour rendering index >80.



Selectable colour temperature.





LED specifications.





Photobiological risk RG1





 In compliance with current thermal regulation (France).


 Test on 850°.


 Product can be covered after installation with insulation. (not blown)


 Product can be covered after installation with insulation. (unrolled or blown)


 Luminaire with a 230V LED module.


 The product is dimmable.

 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replacement source or driver available separately.

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.