
LIGHTING

BRAVA RD-230



- 2700K, 3000K or 4000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Can be covered with peeled or blown insulation.
- Automatic double terminal block.
- Does not require a converter.
- Dimmable.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.





RE

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO54405	MATT BLACK	ALU.+COMPOSITE	AC 230V	5W	2700-3000-4000K	680 Lm (4000K)	615 Lm (4000K)
DO54430	MATT WHITE	ALU.+COMPOSITE	AC 230V	5W	2700-3000-4000K	680 Lm (4000K)	615 Lm (4000K)





MATT BLACK

MATT WHITE



Recessed ceiling mounting only.



Indoor use only



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.





Live parts are equipped with additional isolation protection, such as reinforced or double



Hole cut to insert luminaire (68mm)



Minimum ceiling height to insert luminaire. (50mm)



Beam 60°.



Product in conformity CE.



Colour rendering index >80.



Selectable colour temperature.



LED LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation (France).



Test on 850°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)



LED Luminaire with a 230V LED module.

TECHNICAL DATA

INDOOR

SPOTS





The product is dimmable.



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Non-replaceable light source.